

ANTI – GLARE SYSTEM

EN 12676 certified

MAIBACH®
www.maibach.com



1200 mm 900 mm 600 mm

The original MAIBACH system:

- Durable HDPE vanes
- UV stable, wind and fracture resistant
- Height 1200 mm, 900 mm and 600 mm
- Width 220 mm



Example of an installation on SR Eco

- Certified according to anti-glare norm EN 12676
- Standard distance between vanes: 66 cm
- Standard colour: green (similar RAL 6011)
Other colours available at request
- Suitable for all guardrails:
Connecting brackets are available for any system.



Example of an installation on concrete walls



Connecting bracket: Examples for C-post, Sigma post and concrete




ANTI-GLARE SYSTEM

EN 12676 certified

MAIBACH®
www.maibach.com

Components for Installation on guardrail:

- 1: Support tube with vane holders
- 2: Connecting bracket
(to connect tube and guardrail post)
- 3: Vane with fitting parts for support tube
- 4: Installed anti-glare system



Components for Installation on concrete:

Option 1:

Installation with support tube and connecting bracket
(identical with guardrail installation)

Option 2:

Installation with single vane holder
(individual installation of each vane)



Option 1

Installation with support tube



Option 2

Installation with single vane holder

Optional colour example: grey
(more colours are available at request)



Optional purpose of use:
Vanes mounted at 45° angle



Optional purpose of use:
Pedestrian barrier (vanes in close distance)



MAIBACH VuL GmbH
Bannholzstrasse 4
D-73037 Göppingen / Germany
Phone: +49 7161 99 76 0
e-mail: info@maibach.de
www.maibach.com